

Data sheet

NT A

PRODUCT DESCRIPTION

Alternating current conveyor belt.



MAIN FEATURES

- PVC conveyor belt, closed loop
- Brushless motor with drive board (optional)
- Variable speed adjustment (only if combined with brushless or asynchronous motor with inverter)
- Power supply: 380 V (Hz 50/60) with start button
- Power supply: 220 V (Hz 50/60) with inverter (optional)
- Structure and carpentry belt in stainless steel and anodized aluminum
- Transport from 1 g to 50 kg

DIMENSIONS

SERIES 230	230x1000	-	230x1500	-	230x2000	230x2500	230x3000	230x3500	230x4000	-
SERIES 275	275x1000	-	275x1500	-	275x2000	275x2500	275x3000	275x3500	275x4000	-
SERIES 320	320x1000	-	320x1500	-	320x2000	320x2500	320x3000	320x3500	320x4000	-
SERIES 420	420x1000	-	420x1500	-	420x2000	420x2500	420x3000	420x3500	420x4000	-
SERIES 510	510x1000	-	510x1500	-	510x2000	510x2500	510x3000	510x3500	510x4000	-
SERIES 580	-	-	-	-	580x2000	-	580x3000	-	-	580x4500
SERIES 700	-	700x1400	-	700x1600	-	-	-	-	-	-



Technical specifications and images may be subject to improvements and modifications without notice.



R.S. Bilance S.r.l.
Via Rinaudo, 19, Valcorrente - 95032 Belpasso CT
Tel. +39 095 3523283
commerciale@rsbilance.com
www.rsbilance.com